



## PUMP GROUP WITH 35-60°C THERMOSTATIC MIXING VALVE (ENBOX TM3560 CODE: 201) WITH WITA HE 25-60 180 PUMP





TM 3560 pump group - designed for heating systems in modern and traditional boiler rooms. The pump group is a factory-new set of devices equipped with a modern WITA pump. It is fitted with ESBE thermostatic mixing valve ensuring optimum performance of the circuit. Thermometers in ball valves allow controlling the temperature, and additionally a non-return valve is built in at the low parameter to prevent backflow. The whole group is enclosed in thermal insulation made of EPP. The device is intended both for the manifold and wall installation.

Parameter	Value
Dimensions	470 x 245 x 160 mm
Connections	
- installation side	1'' Female
- boiler side	6/4'' Male
Spacing	125 mm
Max. operational temperature	110°C
Thermometer scale	0-120°C
Check valve	Yes - (in the ball valve at low
	parameter)
Max. pressure	6 bar
Pump type	WITA HE OEM 4 25-60 180
EEI	≤0,20
Pump installation length	180 mm
Mixing valve	ESBE VTA 322 (Scale: 35-60°C)
KVS of the valve	1,6
	Valves - Brass
Body material	Piping - Copper + Brass+ cast iron,
	powder coated
Insulation material	EPP
Sealing	EPDM, Klingierite
components	
Medium	Water or Water-Glycol



- 1. WITA HE OEM4 25-80 180 PUMP
- 2. HIGH PARAMETER BALL VALVE
- 3. LOW PARAMETER BALL VALVE
- 4. LOW PARAMETER 0-120°C CONTACT THERMOMETER
- 5. HIGH PARAMETER 0-120°C CONTACT THERMOMETER
- 6. LOW PARAMETER CHECK VALVE WITH MANUAL LOCK
- 7. BRASS FITTINGS
- 8. ESBE 35-60°C THERMOSTATIC VALVE
- 9. PIPING SECTION ON LOW PARAMETER